

NOTES:

1) CLOSED CELL EPDM SPONGE RUBBER (0.250 G/CM<sup>3</sup>)







REVISION BLOCK			ON BLOCK	PROPRIETARY AND CONFIDENTIAL:	UNLESS OTHERWISE SPECIFIED:		TITLE:				
REV.	DATE	ATE R. BY CHANGES MADE		THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE	DIMENSIONS ARE IN INCHES TOLERANCES PER ARPM CLASS 3			RE-126			
Α				PROPERTY OF UNI-GRIP,INC. ANY REPRODUCTION IN PART OR AS A	WEIGHT				KL-120		
В				WHOLE WITHOUT THE WRITTEN PERMISSION OF UNI-GRIP.INC. IS	0.016 LB/FT						
С				PROHIBITED.	ASTM D1056 2A2		SIZE	DWG. NO.			REV
D				DOCUMENT CONTROL NUMBER	ASTM D2000		Δ		UG-1-RE-126		
E				UG-1-EN-001-FR-(080918)	N/A						
P:\Er	P:\Engineering\Prints\Master Prints\Rubber Extrusion\RE-126 UG-1-RE-126					1	DR. BY C	. VENT	DATE 3/3/2022	SHEET	1 OF 1