



NOTES:

1) CLOSED CELL EPDM SPONGE RUBBER (0.450 G/CM³)

2) 3/8" 3M HEAT ACTIVATED TAPE (0.006 LB/FT)



UNI-GRIP, INC.

9823 STATE ROUTE 53 N
UPPER SANDUSKY, OHIO 43351

REVISION BLOCK				PROPRIETARY AND CONFIDENTIAL:	UNLESS OTHERWISE SPECIFIED:	TITLE:				
REV.	DATE	R. By	CHANGES MADE	THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF UNI-GRIP, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF UNI-GRIP, INC. IS PROHIBITED.	DIMENSIONS ARE IN INCHES TOLERANCES PER ARPM CLASS 3	TS-031				
A										
B					WEIGHT	0.034 LB/FT				
C					ASTM D1056	2A4				
D					ASTM D2000	N/A				
E				DOCUMENT CONTROL NUMBER	UG-1-EN-001-FR-(080918)					
P:\Engineering\Prints\Master Prints\Tape Seals\TS-031 UG-1-TS-375-TP-031				SCALE:	1:1	DR. BY	C. VENT	DATE	8/9/2021	SHEET 1 OF 1